

## HIIO LED High Bay, Selectable Kelvin and Wattage 135/180/240



**SKU:** AF55XLED4650V24445WT

**Product Tags:** [High Bay](#), [LED high bay](#), [LED high bay light](#)

**Product Page:**

<https://www.accessfixtures.com/p/hiio-led-high-bay-135-180-240w-selectable-kelvin-and-wattage/>

Product Description  
HIIO LED High Bay Features:

Selectable Wattage  
- 135/180/240w

Selectable Kelvin

- 4000K, 4500K, 5000K - Diameter: 11.57" - 294mm - Height: 5.83" - 148mm not including hook mount - White finish - UL, DLC, and CUL listed for damp locations - RoHS compliant - IP65 rated - Die-cast aluminum body - Next-generation LED chip - 0-10v dimmable - 6KV surge protector - Acrylic reflector, AL reflector - Type V distribution - 80+ CRI - Built-in heat sink

Built-in die-cast aluminum hook for a strong and easy installation

- optional S hook or 3/4" pendant adapter - Optional bi-level motion sensor for easy installation and additional utility cost savings - Quick-disconnect cable - allows for separating the driver from the LED module for easy maintenance - Ease access for wattage and CCT tuning

Lumen output:

- 125 LPW - 31,567 lumens - Easy opening for maintenance - Optional 120-277v occupancy sensor - -40° C starting temp

HIIO LED High Bay Options:

- 120-277v OCC sensor Access Fixtures Warranty

Access Fixtures is proud to assemble high quality, long lasting lighting products which are covered by a 5-year warranty. In accordance with our warranty policy, we will offer repair, replacement, or refund for qualifying claims. Please contact our friendly customer service team, located in Worcester, MA, to address any questions or concerns you may have. We can be reached at 800-468-9925 Monday-Friday 9-5 EST or via email at [sales@accessfixtures.com](mailto:sales@accessfixtures.com). Click [here](#) to view Access Fixtures' [complete warranty policy](#). Need a Photometric Analysis for Your HIIO LED High Bay Project?

A photometric analysis creates a computer simulation of a particular project. No matter what you are lighting, a photometric analysis is an easy way to quantify light levels before purchasing. When a report is generated, a lighting specialist will walk you through it so you know exactly what you will be receiving. Photometric studies include average and minimum footcandles, uniformity ratios, spacing, light trespass info, and more. Plus, the cost of the study is refunded back to you when

you purchase the fixtures. Call us at 800-468-9925 for more information about ordering a photometric analysis for your project.


Ready to Order or Speak to a Lighting Specialist?

You can place your order online, here. Or, if you want additional information, give us a call at 800-468-9925. Does your project require multiple fixtures? Ask us about quantity discounts. Our team of friendly expert lighting specialists are available to provide what you need to purchase fixtures and illuminate your project with confidence.


## Product Attributes

- Dimensions: 13 &times; 13 &times; 9 in
- Weight: 12 lbs
- Availability: Typically ships in 5-7 business days
- Light Source: 4000K - Cool White, 4500K, 5000K - Bright White
- Available Finishes: White
- Color Rendering Index (CRI): 80+
- Housing: Die cast aluminum housing
- Listings: CuL Listed, DLC Listed, IP65, UL
- Light Source Lumens: 31,567
- Mounting: Hook Mount
- Product Family: H110
- System Watts: 180, 240, 135
- Voltage: 120v, 208v, 240v, 277v
- Warranty: 5-Year Limited Warranty

## Product Gallery



5.83"  
(148mm)  
7.52"  
(191mm)



9.67"  
(245.5mm)





