

**SPEC
SHEET**

FWC Certified

HEZE

LED Wall Pack



AccessFixtures.com

1

FWC Certified:

The 590 nanometer light and included shield make this fixture FWC Certified and turtle friendly.

2

EXTREME-LIFE:

L70 rated life of 213,000 hours. This means that after 213,000 hours this fixture will still deliver 70% or more of its initial lumens – making it virtually maintenance-free.

3

Durable Housing:


Durable Housing: Die cast hinged and gasketed aluminum front frame and housing with ½" coin plugs. Nickel-plated stainless steel hardware. Photocell adaptable.

highlights



Dimensions

Width (D)	14 1/2" (362mm)
Length (B)	11 1/4" (289mm)
Height (A)	9 1/2" (232mm)



PH: 800-468-9925

Sales@AccessFixtures.com

AccessFixtures.com



AccessFixtures
High-Performance Lighting Solutions

Light Source	LED
Kelvin	Amber
Watts	25w, 40w
Available Finishes	Textured Architectural Bronze Powdercoat Finish Over a Chromate Conversion Coating. Custom Colors Available Upon Request
Housing	Die Cast Hinged and Gasketed Aluminum Front Frame and Housing with ½" Coin Plugs. Nickel-Plated Stainless Steel Hardware
Mounting	Cast-in Template for Mounting Directly Over a 4" Recessed Outlet Box, or Use ½" Surface Conduit
Lumens	Up to 794
LPW	32
Lens	Tempered clear flat glass lens
Driver	Electronic Driver, 120-277V, 50/60Hz or 347-480V, 50/60Hz
Dimensions	9½" L x 8¾" W x 12½" H
Listings	CSA, IP65, ANSI/UL
Voltage	120-277v, 347-480v
Photocell	Photocell Adaptable
Warranty	5-year limited warranty



AccessFixtures

High-Performance Lighting Solutions

HEZE OPTIONS

OPTIONS

- 20KA Surge Protection
- 90min Emergency battery backup

SPECTRAL CHART

