

SPEC SHEET

TRID

LED Wall Pack



AccessFixtures.com

1 EXTREME-LIFE:

L70 rated life of 320,000 hours. This means that after 320,000 hours this fixture will still deliver 70% or more of its initial lumens. Extreme reliability and virtually no maintenance.

2 Choice of Lens:

This wall pack comes with a choice of a glare-free opal polycarbonate lens.

3 Unique Design:


TRID's unique triangular design adds architectural interest and appeal in a small package.

highlights



Dimensions

Width (D)	12 1/2" (318mm)
Length (B)	6 1/2" (168mm)
Height (A)	10 1/2" (262mm)



PH: 800-468-9925
Sales@AccessFixtures.com
AccessFixtures.com



AccessFixtures
High-Performance Lighting Solutions



TRID FEATURES

Light Source	LED
Kelvin	3000K, 4000K, 5000K
Watts	16w
Available Finishes	Bronze, Custom RAL
Housing	Die-cast aluminium housing
CRI	80+
Lumens	1,913
BUG rating	B0, U1, G1
Lens	Clear molded UV-stabilized polycarbonate or SoftLED lumaLens UV-stabilized polycarbonate opal
Dimensions	12.5" x 6.75" x 10.25"
Listings	CSA, IP66
Product Family	TRID
Voltage	120-277v
Mounting	Mount directly over a 4" recessed outlet box, includes easy-hang "two hands free" wall mounting bracket with built-in level. No surface conduit entrance.
Warranty	5-year limited warranty





AccessFixtures

High-Performance Lighting Solutions

TRID OPTIONS

OPTIONS

- Choice of 3000K, 4000K or 5000K
- Choice of bronze, or custom RAL
- Choice of opalescent or clear lens
- Surge Protection
- Motion Sensor with dimming
- Button Photocell

