



Luminaire list								
Index	Manufacturer	Article name	Item number	Luminous flux	Light loss factor	Connected load	Quantity	Mounting Height
A	Access Fixtures	230V 50Hz 600W	STAK AF77XST-RSL600S 25'	70760 lm	0.80	618.1 W	16	70'
B	Access Fixtures	230V 50Hz 400W	STAK AF77XST-RSL400S 25'	47814 lm	0.80	407.1 W	2	70'

Name	Parameter	Min	Max	Average	Mean/Min	Max/Min
Target Green 1	Perpendicular illuminance (Adaptive)	9.13 fc	13.7 fc	11.1 fc	1.22	1.50
Target Green 2	Perpendicular illuminance (Adaptive)	11.5 fc	20.1 fc	15.6 fc	1.36	1.75
Target Green 3	Perpendicular illuminance (Adaptive)	12.7 fc	32.3 fc	21.4 fc	1.69	2.55
Target Green 4	Perpendicular illuminance (Adaptive)	12.2 fc	18.8 fc	15.9 fc	1.30	1.54
Target Green 5	Perpendicular illuminance (Adaptive)	7.40 fc	11.2 fc	8.94 fc	1.21	1.52
Target Green 6	Perpendicular illuminance (Adaptive)	7.38 fc	14.5 fc	11.7 fc	1.58	1.97
Target Green 7	Perpendicular illuminance (Adaptive)	8.02 fc	11.6 fc	9.72 fc	1.21	1.45
Distance Marker 1 (Vertical illuminance)	Perpendicular illuminance (Adaptive)	28.8 fc	29.0 fc	28.9 fc	1.003	1.006
Distance Marker 2 (Vertical illuminance)	Perpendicular illuminance (Adaptive)	7.75 fc	7.79 fc	7.77 fc	1.002	1.005
Distance Marker 3 (Vertical illuminance)	Perpendicular illuminance (Adaptive)	14.5 fc	15.1 fc	14.8 fc	1.018	1.038
Distance Marker 4 (Vertical illuminance)	Perpendicular illuminance (Adaptive)	28.4 fc	29.7 fc	29.0 fc	1.021	1.045
Distance Marker 5 (Vertical illuminance)	Perpendicular illuminance (Adaptive)	27.3 fc	27.3 fc	27.3 fc	1.000	1.000
Distance Marker 6 (Vertical illuminance)	Perpendicular illuminance (Adaptive)	12.8 fc	13.0 fc	12.9 fc	1.009	1.016
Distance Marker 7 (Vertical illuminance)	Perpendicular illuminance (Adaptive)	25.6 fc	25.6 fc	25.6 fc	1.000	1.000