

## COZU Industrial Linear Fixture

The COZU Industrial Linear Fixture is a climate proof industrial strength LED fixture available in five wattages.

**Climate Proof:** This fixture is IP65 rated, waterproof, and dustproof for any environment.

**Broad Light Distribution:** COZU's diffuser lens directs light in a wide 120 degree beam.

**Low Profile and Flexible:** Surface mount the COZU for minimal profile or choose the optional wire suspension mount package.



IP65

## Features:

COZU Linear Fixture	COZU 20	COZU 40	COZU 50	COZU 60	COZU 100
<b>SKU</b>	AF38XVPL-LN-20WAN	AF38XVPL-LN-40WAN	AF38XVPL-LN-50WAN	AF38XVPL-LN-60WAN	AF38XVPL-LN-100WAN
<b>Length</b>	2 feet	4 feet	4 feet	5 feet	8 feet
<b>Finish</b>	White powdercoat	White powdercoat	White powdercoat	White powdercoat	White powdercoat
<b>Color Rendering Index (CRI)</b>	80+	80+	80+	80+	80+
<b>Color Temperature (Kelvin)</b>	5000K	5000K	4000K/5000K	5000K	4000K/5000K
<b>Housing</b>	Die-cast aluminum	Die-cast aluminum	Die-cast aluminum	Die-cast aluminum	Die-cast aluminum
<b>Lens</b>	120 degree optics	120 degree optics	120 degree optics	120 degree optics	120 degree optics
<b>LED Type</b>	LED array	LED array	LED array	LED array	LED array
<b>System Watts</b>	20	40	50	60	40
<b>Luminaire Lumens</b>	2,400	4,800	6,000	7,200	12,000
<b>Mounts</b>	Surface or wire mount	Surface or wire mount	Surface or wire mount	Surface or wire mount	Surface or wire mount
<b>Rated Life</b>	50,000 hours	50,000 hours	50,000 hours	50,000 hours	50,000 hours
<b>Operating Temperature</b>	-40F~140F	-40F~140F	-40F~140F	-40F~140F	-40F~140F
<b>Voltage</b>	120-277v	120-277v	120-277v	120-277v	120-277v
<b>Listings and Ratings</b>	IP65, DLC, ETL, CE, RoHS	IP65, DLC, ETL, CE, RoHS	IP65, DLC, ETL, CE, RoHS	IP65, DLC, ETL, CE, RoHS	IP65, DLC, ETL, CE, RoHS
<b>Warranty</b>	5 Year Limited	5 Year Limited	5 Year Limited	5 Year Limited	5 Year Limited