

CURV

L70
25°C **147,000 Hours**

CURV features unique modern elegance, ample efficient LED light, and EXTREME LIFE LED technology. The specially designed UV- stabilized polycarbonate optics offer full-cutoff, excellently controlled uniform lighting.

Specifications and Features:

Housing:

Durable One-Piece Sand Cast Aluminum Housing Features 1/2" Thick Walls. Includes Flush Mounting Base & Vandal-Resistant Screws, Internal Driver Tray for Easy Maintenance.

Listing & Ratings:

CSA: Listed for Wet Locations, ANSI/UL 1598, 8750
IP65

Finish:

Textured Architectural Bronze or Black Powdercoat Finish Over a Chromate Conversion Coating. Custom Colors Available Upon Request.

Lens:

Clear UV-Stabilized Polycarbonate Vandal-Resistant Lens

Mounting Options:

Mounting Kit with 8" Zinc-Plated Anchor Bolts, Included.

LED:

Aluminum Boards

Wattage:

12w: Array 12w, System 13.6w;
18w: Array 18.2w, System 20.4w


Driver:

Electronic Driver, 120-277V, 50/60Hz; Less Than 20% THD and PF>0.90. Standard Internal Surge Protection 2kV. 0-10V Dimming Standard for a Dimming Range of 100% to 10%; Dimming Source Current is 150 Microamps.

Warranty:

5-Year Warranty for -40°C to +50°C Environment.

See Page 2 for Projected Lumen Maintenance Table.



Dimensions

Height (A)	36" (915mm)
Height (B)	32 1/2" (824mm)
Base² (C)	6" (155mm)
Width (D)	1 1/4" (362mm)

Order Information Example:

B9QC1X18U5KCZSP

Model	Optics	Wattage	Driver	CCT	Lens	Color	Options
AF33XB9Q	C		U		C		
AF33XB9Q = CURV EXTREME LIFE LED Bollard Light	C =Type III	1X12 =12w 1X18 =18w	U =120-277V	3K =3000K 4K =4000K 5K =5000K	C =Clear UV-Stabilized Polycarbonate Vandal-Resistant Lens	Z =Bronze B =Black C =Custom (Consult Factory)	SF =Single Fuse (120-277V Only) DF =Double Fuse (120-277V Only) SP =Surge Protection GF1 =GFCI Outlet, 15A, 120V (Side Mount Only)

Project Information:

Project Name: _____ Fixture Type: _____

Complete Catalog #: _____ Date: _____

Comments: _____

Certification & Listings:



Specifications subject to change without notice. Rev. 092520

Accessories & Replacement Parts:



AF33XBREBASE*

*Shown Mounted



AF33XBOADP1

Mounting Accessories (Order Separately, Field Installed)


SIRU SIRU Bollard Retrofit Base Kit Adapts New Bollards to Most Existing Bolt Patterns. Fits all Access Fixtures 7" and a few more Bollards. Die Cast with Powdercoat Finish, Hardware Included. 1 1/2" Dia. x 1 1/2" H

*Specify Color: Z=Bronze, B=Black, C=Custom (Consult Factory)

Replacement Parts (Order Separately, Field Installed)

AF33XB9LFB	Lens Frame, Black Finish
AF33XBOADP1	Adapter Plate with Gaskets for Outlet Boxes. Die Cast with Bronze Powdercoat Finish.

Photometric Data



AF33XB9QC1X18U5K

Grid in feet, Mounting Height = 3 ft.

Photometric Performance


Optic	Wattage (Catalog Logic)	12W (1X12)	18W (1X18)
	Input Watts	13.6W	20.4W
Clear Glass	CCT	Delivered Lumens	
	3000K	1,427	2,140
	4000K	1,548	2,322
	5000K	1,612	2,418
	BUG Rating	B1-U0-G1	B1-U0-G1

Projected Lumen Maintenance

Data shown for 5000 CCT		Compare to MH				
TM-21-11	Input Watts	Initial	25,000 Hrs	50,000 Hrs	100,000 Hrs	Calculated LED Life
L70 Lumen Maintenance @ 25°C / 77°F	All wattages up to and including 20w	1.00	0.96	0.92	0.85	196,000
L70 Lumen Maintenance @ 50°C / 122°F		1.00	0.90	0.81	0.62	78,000
L80 Lumen Maintenance @ 40°C / 104°F		1.00	0.96	0.85	0.92	126,000

NOTES:

1. Projected per IESNA TM-21-11. Data references the extrapolated performance projections for the 525mA base model in a 25°C ambient, based on 10,000 hours of LED testing per IESNA LM-80-08.
2. Compare to MH box indicates suggested Light Loss Factor (LLF) to be used when comparing to Metal Halide (MH) systems.



CURV Base Drawings and Dimensions

